



FLEXTRED™ S3S VEILIGHEIDSSCHOENEN ZWART 1L110133 ESD SC FO SR



**ENERGY
FOAM**



**ROLLCAGE™
stabilizer**



**STEP-
RELEASE™**



Vetervak



PS
Niet-metalen
perforatiebestendige
tussenzool en
inlegzool



SC
Slijtvaste
teenbescherming



FO
Bestand
tegen olie



SR
Getest op
slipweerstand
op een
keramische
tegelvloer
met glycerine

KENMERKEN

- Flexibele en lichtgewicht allround veiligheidsschoenen voor de bescherming van vakmensen.
- ENERGY FOAM hielpolstering voor superieure energieruggave en maximaal comfort.
- STEP-RELEASE™ hiel voor het gemakkelijk uittrekken van de schoen.
- ROLLCAGE™ hielstabilisator voor uitstekende stabiliteit, zelfs op veeleisend terrein.
- Vetervak voor het opbergen van veters om onbedoeld openen, struikelgevaar en schade aan de veters te voorkomen.
- Nubuck waterafstotend lederen bovenwerk om te beschermen tegen water, stof en vuil.
- Scuff cap voor betere bescherming en duurzaamheid van de veiligheidsneus.
- Metaalvrije constructie om gemakkelijk door veiligheidspoortjes te komen.
- Superieure grip om uitglijden te voorkomen.
- ESD (elektrostatische ontlading) gecertificeerd.
- Gecertificeerd volgens EN ISO 20345:2022 S3S ESD SC FO SR.
- Beschikbare maten: 36-48.

**STAY SAFE.
STAY PRODUCTIVE.**



Disclaimer

Information present within
this sheet was correct at
the date of issue.

Techtronic Industries GmbH

71364 Winnenden
Germany

nl.milwaukeetool.eu



FLEXTRED™ S3S VEILIGHEIDSSCHOENEN ZWART 1L110133 ESD SC FO SR



TECHNISCHE INFORMATIE

Artikelnummer 4932493714

Type schoen Laag model

Metaalvrij Ja

Schoenmaat (EU/UK) 36/3

Verpakkingsstijl Kartonnen doos

Packaging [innerlmaster] 1/10

GEBRUIKSAANWIJZING

The shoes shall only be used as safety shoes. Using the shoes beyond this application area is not permissible. Depending on the version, the shoes shall be protected against such risks as moisture, impacts in the toe area (impact and pressure forces), perforation of foreign objects through the sole, slipping, electric properties, light cuts on the boot shaft sides, heat and cold.

INSTRUCTIES VOOR OPSLAG

Regular maintenance of safety shoes is essential to ensure their continued effectiveness. Clean shoes regularly using a soft brush and mild soap. Avoid using harsh chemicals or solvents as they may damage the shoes. Inspect shoes regularly for any signs of damage or wear and replace if necessary. Store safety shoes in original package in a dry, cool place, away from direct sunlight or heat sources. Avoid storing shoes in damp or humid conditions, as this may cause damage or deterioration. Do not store shoes in areas where they may be exposed to chemicals or other hazardous substances.

VEROUDERINGSTERMIJN

It is not recommended to store the product for more than 5 years. It is recommended to replace safety shoes every 12 months, or sooner if they become damaged or worn.

**STAY SAFE.
STAY PRODUCTIVE.** 

Disclaimer
Information present within
this sheet was correct at
the date of issue.

Techtronic Industries GmbH
71364 Winnenden
Germany
nl.milwaukeetool.eu