



****FLEXTRED™ S1PS VEILIGHEIDSSCHOENEN HIGH VIS SC FO SR ESD****



**ENERGY
FOAM**



**ROLLCAGE™
stabilizer**



**STEP-
RELEASE™**



Vetervak



PS
Niet-metalen
perforatiebestendige
tussenzool en
inlegzool



SC
Slijtvaste
teenbescherming



FO
Bestand
tegen olie



SR
Getest op
slipweerstand
op een
keramische
tegelvloer
met glycerine

KENMERKEN

- Flexibele en lichtgewicht allround veiligheidsschoenen voor dagelijks professioneel gebruik.
- Reflecterende elementen aan de hiel en voorzijde, gecombineerd met reflecterende accenten in het materiaal voor betere zichtbaarheid en veiligheid op de werkplek.
- ENERGY FOAM-demping in de hiel voor uitstekende energieruggave en maximaal comfort.
- STEP-RELEASE™-hiel voor snel en eenvoudig uittrekken van de schoen.
- ROLLCAGE™-hielstabilisator voor uitstekende stabiliteit, zelfs op veeleisend terrein.
- Veterzakje om de veters veilig op te bergen en zo losraken, struikelgevaar en beschadiging van de veters te voorkomen.
- Ademend textiel voor goede ventilatie en comfort gedurende de hele dag.
- Versterkte voorzijde ter bescherming van de neus tegen slijtage.
- Metaalvrije constructie voor eenvoudig passeren van beveiligingspoorten.
- Uitstekende grip voor extra stabiliteit en zekerheid.
- ESD-gecertificeerd.
- Gecertificeerd volgens EN ISO 20345:2022+A1:2024 S1PS SC FO SR ESD.
- Beschikbare maten: 36-48.

**STAY SAFE.
STAY PRODUCTIVE.**



Disclaimer

Information present within
this sheet was correct at
the date of issue.

Techtronic Industries GmbH

71364 Winnenden
Germany

nl.milwaukeetool.eu



****FLEXTRED™ S1PS VEILIGHEIDSSCHOENEN HIGH VIS SC FO SR ESD****



TECHNISCHE INFORMATIE

Artikelnummer 4932501454

Type schoen Laag model

Metaalvrij Ja

Schoenmaat (EU/UK) 36/3

Verpakkingsstijl Kartonnen doos

Packaging [innerlmaster] 1/6

GEBRUIKSAANWIJZING

The shoes shall only be used as safety shoes. Using the shoes beyond this application area is not permissible. Depending on the version, the shoes shall be protected against such risks as moisture, impacts in the toe area (impact and pressure forces), perforation of foreign objects through the sole, slipping, electric properties, light cuts on the boot shaft sides, heat and cold.

INSTRUCTIES VOOR OPSLAG

Regular maintenance of safety shoes is essential to ensure their continued effectiveness. Clean shoes regularly using a soft brush and mild soap. Avoid using harsh chemicals or solvents as they may damage the shoes. Inspect shoes regularly for any signs of damage or wear and replace if necessary. Store safety shoes in original package in a dry, cool place, away from direct sunlight or heat sources. Avoid storing shoes in damp or humid conditions, as this may cause damage or deterioration. Do not store shoes in areas where they may be exposed to chemicals or other hazardous substances.

VEROUDERINGSTERMIJN

It is not recommended to store the product for more than 5 years. It is recommended to replace safety shoes every 12 months, or sooner if they become damaged or worn.

**STAY SAFE.
STAY PRODUCTIVE.** 

Disclaimer
Information present within
this sheet was correct at
the date of issue.

Techtronic Industries GmbH
71364 Winnenden
Germany
nl.milwaukeetool.eu