

SAFETY JOGGER

INDUSTRIAL

FOOD

X0600 S3

Safety shoe, designed for the food industry

Upper	Nappa Action Leather
Outsole	PU/PU
Toecap	Steel
Midsole	Steel
Lining	Cambrella
Footbed	SJ foam footbed
Standards	S3 / SRC
Size range	EU 36-47 / UK 3.5-12.0 / US 4.0-13.0 / CM 23.5-31.0



BLK



WATER RESISTANT UPPER

More than likely you're going to get caught up in the rain at some point on a regular workday. Safety shoes usually have a water resistant upper (WRU) to protect from the rain.



OIL & FUEL RESISTANT

Oil and fuel resistance has really become a basic feature. Like every Safety Jogger outsole is slip resistant, it is also engineered, tested and proven to be oil and fuel resistant outsole.



S3

The S3 safety shoes are suitable for work in an environment with high humidity and presence of oil or hydrocarbons. These shoes also protect against perforation risk of the sole, and foot crushing.



SRC

Slip resistant soles are one of the most vital elements in safety footwear. SRC slip resistant soles pass both SRA and SRB slip resistant tests, they are tested on both steel and ceramic surfaces.



STEEL TOECAP

Steel toecaps are naturally stronger than composite toecaps, a thinner layer is used in the work boots to reach the same strength as a composite toe. They are cheaper compared to composite toes and are conducting cold, heat and electricity.



STEEL MIDSOLE

Puncture resistant steel midsoles are made from stainless or coated steel. They are less flexible than Aramid soles but they offer a higher level of protection.

FOOD

X0600 S3

Industries:

Automotive, Catering, Cleaning, Construction, Food & beverages, Logistics, Production

Environments:

Wet

Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.



	Description	Measure unit	Result	EN ISO 20345
Upper	Nappa Action Leather			
	Upper: permeability to water vapor	mg/cm ² /h	1.0	≥ 0.8
	Upper: water vapor coefficient	mg/cm ²	18.2	≥ 15
Lining	Cambrella			
	Lining: permeability to water vapor	mg/cm ² /h	95.9	≥ 2
	Lining: water vapor coefficient	mg/cm ²	480	≥ 20
Footbed	SJ foam footbed			
	Footbed: abrasion resistance	cycles	400	≥ 400
Outsole	PU/PU			
	Outsole abrasion resistance (volume loss)	mm ³	81.9	≤ 150
	Outsole slip resistance SRA: heel	friction	0.35	≥ 0.28
	Outsole slip resistance SRA: flat	friction	0.35	≥ 0.32
	Outsole slip resistance SRB: heel	friction	0.14	≥ 0.13
	Outsole slip resistance SRB: flat	friction	0.18	≥ 0.18
	Antistatic value	MegaOhm	26.2	0.1 - 1000
	ESD value	MegaOhm	N/A	0.1 - 100
	Heel energy absorption	J	28	≥ 20
Toecap	Steel			
	Impact resistance toecap (clearance after impact 100J)	mm	N/A	≥ 14
	Compression resistance toecap (clearance after compression 10kN)	mm	N/A	≥ 14
	Impact resistance toecap (clearance after impact 200J)	mm	15.0	≥ 14
	Compression resistance toecap (clearance after compression 15kN)	mm	16.0	≥ 14

Our shoes are constantly evolving, the technical data above may change.

All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.

Sample size: 42