

# SOFTANE™ Tradition

## JALARTIC SAS J0257

Softane™  
Tradition



**S3 CI SRC**  
**EN ISO 20345:2011**  
**36 to 48**

- **Full grain AP 23 leather**
- **Softane™ dual-density sole**

- ❖ Natural-coloured, fur-lined boot with 2 leather side tabs for rapid pull-on.
- ❖ Isothermal lining for better protection against cold.
- ❖ Upper in water and oil resistant full grain **AP 23** leather, exclusive to Jallatte :
  - ❖ **10 to 15%** (2.4 mm) **thicker** than most leathers used for safety footwear.
  - ❖ **Resistance to penetration of water vapour three times higher** than the minimum fixed by European Standard.
- ❖ Flat binding at top of quarters.
- ❖ Counter to maintain a snug-fitting heel.
- ❖ Inlay covering the entire surface of the foot, removable, antistatic, treated against bacteria, containing active carbon, anatomical and with heel cushioning. High capacity for absorbing and evaporating perspiration.
- ❖ Perforated steel toe-cap (patented) – 200 J.
- ❖ Puncture-resistant stainless steel midsole .
  
- ❖ Dual density **Softane™** sole with progressive shock absorber to protect back and joints from vibrations. Self cleaning sole pattern. Multi-directional treads. Rounded heel pressure zone for comfort and stability.

### Slip resistance tests results

EN Standard : EN ISO 20345 : 2011

**Requirement SRC (SRA+SRB)**

**SRA** Test ground : ceramic/lubricant : water and detergent

On flat 0,58 (>0,32) – On the heel 0,54 (>0,28)

**SRB** Test ground steel/lubricant : glycerine

On flat 0,37 (>0,18) – On the heel: 0,14 (>0,13)

- ✓ Wraps round the foot for increased stability when walking.
- ✓ Outsole density = 1.02 / Comfort layer density = 0.45
- ✓ Highly resistant to oils and hydrocarbons.
- ✓ Abrasion resistance : 80 mm<sup>3</sup>
- ✓ Heel shock absorption 29 Joules.



Weight	Gross weight (42): 1760 g / Net weight (42): 1440 g
Size	36 to 48
Packaging	5 pairs
Box shoes (mm)	337 x 328 x 135
Cartons (mm)	625 x 425 x 345